

CONCRETE CUTTER

CAN BE USED ON AN EXTENSIVE RANGE OF MEDIUMS LIKE AGGREGATE CONCRETE, GENERAL MASONRY PRODUCTS ETC

H14/CNQ16 PETROL AND HDL88/CNQ20 DIESEL

MADE TOUGH FOR AFRICA™



- Super-rigid box frame ensures straight cuts while resisting warping and vibration – prolongs cutter life; extends blade life
- Japanese-quality shaft bearings for prolonged service
- Ergonomically-designed, height-adjustable handles with comfortable grips
- Easy crank for raising/lowering cutting depth
- Hinged front, lift-up blade guard is designed to provide easy blade replacement
- Anti-rust watertank provides optimum flow and volume of water to the blade
- Throttle control as standard



Diamond saw blade

Laser-welded diamond saw blade for flat sawing equipment

- Diamond saw blade is an optional extra
- Unit fitted as standard with HOFFMANN 14 hp (9.2 kW) petrol engine
- Also available with HOFFMANN 10 hp (7.5 kW) diesel engine

HOFFMANN POWER

MODEL	CNQ16	CNQ20
Engine type	HX14 - Petrol	HDL88 - Diesel
Engine power kw (hp)	10.4 (14)	7.5 (10)
Weight kg (lbs)	115 (253)	135 (297)
Max cutting depth cm (in)	15 (5.8)	
Blade size cm (in)	30 - 45 (14 - 18)	
Depth adjustment	Handle rotation	
Driving method	Manual push	
Water tank capacity (L)	30	
Packing cm (in)	90.5 x 59 x 108	