

# DRIVE UNIT



Fitted with HOFFMANN petrol engine on swivel base with lock pin drive unit supplied with Dynapac type coupling.



## DRIVE UNIT

MODEL	CNVR
Engine make	HOFFMANN
Engine type	HX6.5 or HY7
Operation mass (kg)	22

Our compact pump has an aluminium cast body and can be used in areas without access to power supply. The pump is driven by a drive unit through a flexible shaft that is connected to the pump.



## SUBMERSIBLE PUMP

(with flexible drive shaft)

MODEL	CNWP/2x6M	CNWP/3x6M
Discharge diameter (mm)	50	75
Capacity (L/ph)	1300	
Maximum head (m)	24	18
Revolution (rpm)	3000 - 3600	
Length of flexible drive shaft (m)	5	
Weight: drive shaft and pump (kg)	21	22

## FLEXIBLE SHAFT POKER

(45 mm x 6 m)



MODEL	CN-32	CN-45
Vibrator head diameter x length (mm)	32 x 442	45 x 442
Vibrator amplitude (mm)	1.25	1.25
Frequency (Hz)	225	
Flexible drive shaft (rpm)	3000 - 3600	
Total length (m)	6	
Nett weight ± (kg)	10	13

# HOFFMANN POWER