

2:1 REDUCTION ENGINES

MADE TOUGH FOR AFRICA™

FULL RANGE OF REPLACEMENT PARTS | LIGHT-WEIGHT AND COMPACT



Centrifugal wet clutch



Double chain

Ideal for:

- Concrete mixers
- Conveyors
- Special applications

HOFFMANN POWER

ENGINE DRAWINGS AVAILABLE ON www.hoffmannpower.co.za

MODEL	HX5.5CLCH	HX5.5 - 2:1DC	HX9CLCH	HX9DC
Engine type	HX5.5 - 2:1DC			
Driving method	Centrifugal clutch	Double chain drive	Centrifugal clutch	Double chain drive
Displacement (cc)	162		270	
Engine speed (rpm)	3600 max/3000 continuous			
Nett power (kW/3600 rpm)	3.6		6	
Nett torque (nm/rpm)	20.6/1250		35.4/1250	
Starting method	Recoil			
Output shaft size (mm)	19.05		25.4	
Fuel tank capacity (L)	4		6.5	
Fuel consumption ± (L p/h)	0.5		0.86	
Recommended fuel type	Unleaded 87			
Lube oil type	SAE 15W40			
Nett weight ± (kg)	19	15.5	28	

We reserve the right to improve or withdraw the specifications or products without prior notice