

SLUDGE PUMPS PETROL/DIESEL DRIVEN

MADE TOUGH FOR AFRICA™

LOW OIL CUT-OUT FITTED TO ENGINE
ISO 9001 CERTIFIED
FULL SPARE PARTS BACK-UP
SOLIDS HANDLING 25 MM


FULL RANGE OF REPLACEMENT PARTS | LIGHT-WEIGHT AND COMPACT

BUILT WITH PROVEN PETROL AND DIESEL ENGINES

- Recoil start in roll-over frame – keyed shaft
- Low fuel consumption
- Easy opening design, complete with fittings (Excl. hose)
- Self-priming
- High performance

Ideal for pumping:

- Dirty water with solids (25 mm)
- Muddy water
- Sewage
- Drain water



for easy initial priming



H-100SP



MODEL	H-100SP
Pump type	Sludge
Suction/discharge diameter [mm (in)]	100 (4)
Maximum capacity (L p/h)	102 000
Total head (m)	30
Suction head (m)	8
Engine speed (rpm)	3600
Nett weight (kg)	95
Engine type	HX14 HX14E / HDK92E

HOFFMANN POWER

ENGINE DRAWINGS AVAILABLE ON www.hoffmannpower.co.za

We reserve the right to improve or withdraw the specifications or products without prior notice